

Sky Farm Estates

STANDARD CONSTRUCTION PACKAGE AND OPTIONAL UPGRADES

SITE & EXCAVATION

- Layout of the foundation and septic system as approved by local and state authorities
- Excavate material to pour footings and walls
- Backfill foundation with appropriate materials
- Excavate and installation of PVC lines for electrical, phone, cable, and water lines
- All disturbed areas will be loamed and hydro seeded (hydro seed is not warranted)

FOUNDATIONS/FLOORS/DRAINS

- Foundation shall be poured concrete approximately eight inches thick with 4000 psi concrete
- Foundation shall be exterior damp proofed according to local building requirements
- Basement / Garage floors shall be poured approximately four inches thick with 3000 psi concrete
- Basement floors shall be prepped for radon gas ventilation system
- Exterior footing drains shall be four inch in diameter plastic perforated pipe. The drain shall be covered with approximately 4-6 inches of ¾ inch stone and fabric, and gravity fed from the house to daylight where ever possible
- All non walkout basements shall include steel factory primed bulkhead.

FRAMING

- Sills: are pressure treated 2x6 with foam sill seal between foundation and sill
- Floor joists: Spruce fir joist spaced 16oc or per plan
- Floor sheathing: ¾" Advantech tongue and grove glued and ring nailed
- Exterior walls: framed 2x6 x16 inch on center
- Exterior sheathing: 7/16 osb
- Interior walls: 2 x 4 x 16 inch on center
- Ceiling joists: 2x8 x16 inch on center or per plan
- Rafters: 2x8 x16 inch on center or per plan
- Roof Sheathing: ½ inch CDX plywood
- Venting: Eves vents and ridge venting applied per code

**Note: Floor Joists, ceiling joists and rafters are sized to local and national building code

EXTERIOR TRIM AND FINISH

- Premium vinyl siding 4" wood grain clapboard style (vinyl shakes are an upgrade)
- PVC freeze boards installed (front elevation only)
- Corner boards are 6" vinyl traditional corner boards in white
- Soffits are vented vinyl in white

SKYFARM

WINDOWS & EXTERIOR DOORS

- Windows shall be Harvey Industries energy star rated vinyl double hung, with grills between the glass
- Sizes and quantities shall be based on the plans
- Front Door Colonial style fiberglass insulated door with standard nickel hardware
- Garage Doors- Colonial style white steel doors with openers and two remotes

PLUMBING

- Pex piping for all water lines, PVC waste water piping and, Cast Iron and Flex lines for gas piping
- Hot water 40 gallon Gas fired direct vent high efficient
- Laundry Washer and Dryer hook-ups (gas standard, electric upgrade)
- Sillcocks Frost free one in the front and one in the rear.
- Bath Sinks Under mount in white with standard 2 handle chrome faucet by Moen
- Toilets Standard builder series in white
- Tub / Shower Fiberglass smooth surface in white with standard chrome fixture by Moen or equivalent
- Kitchen sink Standard double bowl stainless steel
- Kitchen faucet Standard chrome w/integrated spray by Moen or equivalent

HVAC (HEATING AND COOLING SYSTEM)

- Forced hot air by gas, 90-95% high efficiency system Lennox or equivalent
- Two zones with digital thermostat controls
- Propane tank buried 500 gallon standard
- Central A/C
- Zero Clearance Fireplace with marble surround

ELECTRICAL

- Electrical wiring- plugs and switches per code
- 200 AMP with service panel and circuit breakers
- Smoke and CO detectors shall be installed per town code
- Exhaust fan/light combination units shall be installed in all bathrooms
- Lighting Standard builder allowance of \$1,000
- One switched outlet per room unless there is an overhead light.
- One standard doorbell
- Three category 5 phone lines and three cable lines with wall jacks
- One basement outlet by the electrical panel
- Two exterior house outlets
- 2 ceiling fans wired only in greatroom & master bedroom

INSULATION

- Flat Ceilings R-38 Fiberglass insulation
- Sloped Ceilings R-38 Fiberglass insulation
- Exterior Walls- R-21 un-faced with 4 mil Poly vapor barrier
- Basement Ceiling R-30 un-faced

SKYFARM

INTERIOR FINISH, DOORS, AND TRIM

- Interior walls Finished with 1/2 inch sheetrock smooth
- Interior Ceilings Finished with 1/2 inch sheetrock, random roll finish
- Interior doors Colonial two panel masonite smooth finish painted
- Hardware Nickel standard builder package knob style
- Interior door/window trim 3 1/4" Stafford casing painted
- Interior base board trim 5 1/4" standard colonial style painted
- · Painting Latex flat finish on the walls with latex semi-gloss finish on the trim
- Dining room shall have 3 1/2" crown molding and chair rail

KITCHEN / BATHROOM CABINETS AND COUNTERTOPS

Standard builder allowance \$10,500.00

INTERIOR STAIRS

- Main stairway shall be finished with oak treads, pine risers and oak railings with pine balusters.
- Basement stairs shall be finished with stair grade plywood treads / risers and standard grade railings

FLOORING

- Hardwood flooring in 1st floor, living room, kitchen, dining area, dining room, entry way and hallways. Flooring is to be Bruce solid wood pre-finished hardwood oak flooring with natural finish - 2 1/4" x 3/4"
- Additional hardwood or tile \$10.00 per sq ft inclusive of flooring credit.
- Carpet in all bedrooms, greatroom,2nd floor hallway and landing at \$20.00 per sq.yd. allowance
- Tile in all bathrooms and laundry room from builder's selection.

APPLIANCES

GE Stove: JGB750SEFSS

GE Microwave: JNM7196SFSS

GE Dishwasher: GDT580SSFSS

SHELVING

- Bedroom closets, pantry and above the washer / dryer shall have standard closet maid shelving
- Builder does not supply any mirrors, towel bars or toilet paper holders

DECKS / PORCHES

Rear Deck shall be 12' x 12' pressure treated off the rear of the house.

DRIVEWAY / FRONT WALKWAY

- Driveway shall have a processed gravel base with one coat of finish asphalt paving
- Walkway shall be asphalt paving leading to the front door and side garage door

LANDSCAPING

- Disturbed areas shall be re-graded, loamed and seeded
- Shrubs to be planted at builders discretion

WATER SUPPLY

Water shall be supplied by private drilled well system.

SWFARM

Available Options

OUTDOOR LIVING & FINISH

	Enlarge the rear deck to (14X16) 14X14 PT Deck off of sunroom Pavers to the front door Granite light post (no fixture) Flood lights Gas grill hook-up on deck	\$ \$ \$ \$ \$	21,000 2,895 5,850 5,200 1,200 225 595 5,000
INTERIOR TRIM & FINISH			
*		\$ \$ \$	750 250 400
FIEGTRICAL			
		\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	125 125 150 85 175 225 125 175 each 375 325
Plumbing			
8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	Jetted tub in master Change all fixtures to satin nickel or oil rub bronze Central vacuum system Tankless hot water system Extra exterior sill cock Whole house humidifier of heating system	\$ \$ \$ \$ \$	2,575 1,800 3,000 3,750 250 1,000
GENERAL			
@ @ @	Standby generator with automatic transfer switch Exterior key pad entry for garage Third bay garage. (Front entry only) Cultured Stone installed on 2X10 front bump out(Bldrs standard) Hip roof style	\$ \$ \$	14,000